



STEAM AGEIG TEST CHAMBER

APPLICATIONS:

Made of stainless sus#340 Easy to operate and set. Controlled by micro computer digital LED. Have time planning function. The maximum setting is 9990 mins. Have safety device including multi over-temperature protection and power off when out of water. Testing high temperature / high humidity to spare parts. connector passive component and semiconductor. digital electronic indicator + SSR with PID automatic calculation capability, the maximum running time is 999 mins. Water system drying out prevention and automatic overheating prevention.

- ▲ **VALUE**
- ▲ **VERSATILITY**
- ▲ **PERFORMANCE**



MODEL : BSA-3

SPECIFICATIONS

	Model	BSA-3
	Inner chamber size WxHxD (mm)	100x540x260, 3 sets
	Exterior chamber size WxHxD (mm)	610x540x340
	Temperature Range	Room temperature +10°C to +98°C
Performance	Temperature control accuracy	±0.3°C
	Temperature resolution	±1°C
	Heat-up Time	45 minutes
Material	Exterior Chamber material	Stainless steel plate + Power Coated
	Interior Chamber material	SUS#304 stainless steel plate
	Insulation	PU & Fiberglass wool
System	Wind Circulation	Sirocco fan
	Heating system	SUS#304 stainless steel high-speed heater
	Controller	Digital controller
	Safety Devices	Overheating circuit-breaker, compressor overload protection, control system overload protection, humidifying system, overheating protection, breakdown indicator light
	Power Supply	AC 1 f 220V, 3 f 380V 60/50Hz
	Customization	Available