



STEAM AGEIG TEST CHAMBER

APPLICATIONS: -

Made of stainless sus#340 Easy to operate and set. Controlled by micro computer digital LED. Have time planning function. The maximum setting is 9990 mins. Have safety device including multi over-temperature protection and power off when out of water. Testing high temperature / high humidity to spare parts. connector passive component and semiconductor. digital electronic indicator

+ SSR with PID automatic calculation capability, the maximum running time is 999 mins. Water system drying out prevention and automatic overheating prevention.



BSA - 3

- **VALUE**
- **VERSATILITY**
- **PERFORMAN**

SPECIFICATIONS

	Model	BSA-3
	Inner chamber size WxHxD (mm)	100x540x260, 3 sets 610x540x340
	Exterior chamber size WxHxD (mm)	Room temperature +10! C to +98! C
Performan	Temperature control accuracy	±0.3°C
	Temperature resolution	±1°C
	Heat-up Time	45 minutes
Material	Exterior Chamber material	Stainless steel plate + Power Coated
	Interior Chamber material	SUS#304 stainless steel plate
	Insulation	PU & Fiberglass wool
System	Wind Circulation	Sirocco fan
	Heating system	SUS#304 stainless steel high-speed heater
	Controller	Digital controller
	Safety Devices	Overheating circuit-breaker, compressor overload protection, control system overload protection, humidifying system, overheating protection, breakdown indicator light
	Power Supply	AC 1! 220V, 3! 380V 60/50Hz
	Customization	Available